

Technical drawing of a 4-port RJ45 patch panel. The drawing includes three views: a front view, a side view, and a top view.

Front View (Top): Shows the panel with 8 ports (4 RJ45 and 4 BNC). Dimensions include a total width of 32, a port spacing of 16, and a port offset of 10. Callouts specify 4-M2x0.4*6L and 6-M3x0.5*6L.

Side View (Right): Shows the panel's profile with a height of 61 and a mounting hole offset of 0.2.

Top View (Bottom): Shows the panel's top with a width of 40 and a height of 20. It includes a 14mm dimension for the mounting hole offset and a 32mm dimension for the port spacing. Callouts specify 4-Ø3.4 and Ø6.5*5L.

一般公差	精加工: $\nabla_{0.05}$	審核	日期	備註事項	成品獨立包裝保存	機種	MC1D-40L	
尺寸範圍	容許差	細加工: $\nabla_{0.3}$	繪圖	日期	表面處理	依各零件	料號	
0.5 ~ 4	+0.05	粗加工: $\nabla_{0.8}$	設計	日期	2008/1/7	材 質	見零件表	
4 ~ 16	+0.07	 Http://www.gmtglobalinc.com 熱情／創新／快樂 GMT 高明鐵企業股份有限公司 GMT GLOBAL INC. TEL: 886-4-7688327 FAX: 886-4-7688315		數量	1 /組	圖 名	X軸車旋鈕齒輪驅動鳩尾薄型滑台	
16 ~ 68	+0.1			熱 處 理	N/A		圖 號	MC1D-40L
68 ~ 250	+0.2			單 位	mm	圖紙尺寸	A4	 版次
250 ~ 1000	+0.3			比 例	1:1	重量	253.92g	
1000 ~ 1500	+0.5							